

## Series Features




- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 0.20 Amps  
277VAC 60 Hz 0.20 Amps



- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- 2DZF-PAR PAR-36 Type, High-Intensity Tungsten Lamps, 6-Watt
- 2DZF-MR MR-16 Type, Halogen Lamps, 5-Watt



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free



- Injection-Molded Thermoplastic Housing
- Snap-Together Design for Fast Installation
- Off-White Finish
- Fully Adjustable Lighting Heads
- Single- or Double-Face Configuration
- Replaceable Knock-Out Directional Chevrons
- Canopy for Surface, End or Ceiling Mount
- LED Charge Rate Indicator
- Damp Location
- Test Switch
- UL Listed

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2DZF-PAR	6	12	-	-	-	-	-	-	-	(1) S65
2DZF-MR	5	12	-	-	-	-	-	-	-	(1) S65

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. NEC requires 1.5 hours of emergency illumination.

## Ordering Information

2DZF	-PAR -MR	-RW -GW	-RMT
Series	Head Type	Letter Color RW – Red GW – Green	Options Factory Options

## 2DZF



2DZF-PAR



2DZF-MR

### Dimensions

#### 2DZF-PAR & 2DZF-MR With Heads on Side

Height: 10.2"  
Width: 21.7"  
Depth: 4.5"

#### With Heads on Top

Height: 15.7"  
Width: 16.3"  
Depth: 4.5"

### Options

Add Suffix to Catalog Number

**-RMT** Remote Capability (Additional 12 Watts at 6VDC)

