























## Series Features

-  ■ 120VAC Operation Standard
-  ■ Maximum Input Rating (120 or 277VAC) 20 Watts
-  ■ Energy-Saving Compact Fluorescent
-  ■ (2) 120VAC, 7-Watt Lamps
- Architectural Grade
- Clean, Contemporary Styling
- Ceiling or Wall Mount
-  ■ Recessed or Surface Housing
-  ■ Etched, Clear Acrylic, Edge-Lit Panel
-  ■ Silk Screened Letters
- Steel Housing and Trim Plate
- White Powder-Coat Finish
- UL Listed

## Additional Emergency Unit Features

-  ■ Dual-Voltage Transformer for 120/277 VAC Operation
-  ■ Integrated Solid State System
-  ■ Constant Current, Automatic Charger No Manual Battery Recycling
-  ■ Lock Out (Automatic Battery Connect)
-  ■ Low-Voltage Battery Cutoff
-  ■ Brownout Sensitivity
-  ■ Maximum Input Rating (120 or 277 VAC) 24 Watts
-  ■ Energy-Saving Xenon
-  ■ (3) Xenon (AC) & (4) HIT (DC) Lamps
-  ■ Full Lumen Output in Emergency Mode
-  ■ Sealed Nickel Cadmium Battery
-  ■ 10-Year Battery Warranty
-  ■ Maintenance-Free
-  ■ Test Switch
-  ■ Red (Power On & Charge) Indicator

### Specify Chevron Configuration on all Edge-Lit Signs

- |                    |   |                                         |         |
|--------------------|---|-----------------------------------------|---------|
| Blank = No Chevron |   | DC = Dual Chevrons                      | < >     |
| CR = Chevron Right | > | CRCL = Chevron Right<br>Chevron Left    | ① > ② < |
| CL = Chevron Left  | < | (Double-Face Only – 1 Chevron per Face) |         |





## Ordering Information

ERX Series	1 # Faces	W Trim Color W hite* B lack B R ass M atte Chrome P M Painted M atte Chrome S S Stainless Steel	R Letter Color R ed G reen	W† Backgrnd. Color Blank – None W – White M B – Mirrored	C Fixture Type C eiling W all	R Mounting Type R ecessed S urface	-PA Options Factory Options
RX – AC	1						
ERX – Emer.	2						

\*Standard †Standard Background Color of Single-Face Sign is Clear (Blank). For Non-Standard Single-Face and All Double-Face Signs, Indicate **W** for White Background or **MB** for Mirrored Background.



RX / ERX



## Dimensions

### RECESSED SIGNS

Rough-In Opening Size:  
4.75" x 14"

## Options

Add Suffix to Catalog Number

- 277** 277VAC Input
- 2CKT** (2) Independent AC Circuits
- E** End Mount (Use Surface Mount – Ceiling as Base Model)
- SALIDA** Spanish Nomenclature
- STAIRS** "STAIRS" Nomenclature

For Ceiling Recessed Mount Models Only:

- HBB** Hanger Bracket Bars (Speed Installation, Provide Housing Adjustment, Can Rotate 90°)
- PA** Plenum Construction

