

Series Features

- 120VAC Operation Standard
- Dual-Voltage Transformer for 120/277 VAC Operation
- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Maximum Input Rating (120 or 277VAC) – 36 Watts



EMERGENCY LIGHT

- (2) 6VDC, 6-Watt HIT Lamps (PH)
- (2) 6VDC, 8-Watt PAR-36 Sealed Beams



EMERGENCY EXIT

- 2ESDX – LED (Indirect) 25+ Years
- (1) Strip, 120/277 VAC, 3.6-Watt



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free Battery



- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- 20-Gauge Steel Housing
- Polycarbonate Lamp Enclosures (-PH)
- White Powder-Coat Finish
- Test Switch
- Red (Power On) LED Indicator
- UL Listed



2ESDX-DH  
Rectangular Heads



2ESDX  
Round Heads

Unit Information

Model Number	Watts per Hour								Replacement Battery
	1.5	2	3	4	5	6	7	8	
2ESDX	32	24	16	12	10	8	7	6	(1) S610SL

Dimensions

**Housing**

Height: 13.3"  
Width: 12.3"  
Depth: 2.3"

(Add 12.5" to the Overall Width Dimension for Round-Head Models)

Options

Add Suffix to Catalog Number

- U Universal Face (Additional Backplate – Double-Face Signs Only.)

Ordering Information

2 Emergency Light	ESDX Series ESDX	1 # Faces	R Letter Color	W† Stencil Color	W Housing Color	-PH Head Type	-OF Options
0		1	R ed	W hite	W hite	Blank – Rnd.	Factory Options
1		2	G reen	B lack	B lack	PH – Plastic Head	Options
2*			W hite	M atte	M atte		
				C hrome	C hrome		

\*Standard

†Background Panel Color on Open-Face Signs

