








## Series Features

- 
  - 120VAC Operation Standard
  - Maximum Input Rating
    - 120VAC 24 Watts
    - 277VAC 30 Watts
- 
  - Long-Life Incandescent
  - (2) 140VAC, 15-Watt Lamps
- 
  - Ceiling, End or Back Mount
  - Canopy
  - Universal Stencil
  - Directional Chevron Snapouts
  - Downlight
  - 20-Gauge Steel Housing
  - White Powder-Coat Finish
  - UL Listed

## Additional Emergency Unit Features

- 
  - Integrated Solid State System
  - Multi-Rate, Controlled, Automatic Charger
  - Lock Out (Automatic Battery Connect)
  - Low-Voltage Battery Cutoff
  - Brownout Sensitivity
  - Dual-Voltage Transformer for 120/277 VAC Operation
  - Maximum Input Rating
    - (120 or 277VAC) 26 Watts
- 
  - Long-Life Incandescent
  - (2) 6VDC, 6-Watt Lamps
- 
  - Sealed Lead Calcium Battery
  - 6-Volt Operation
  - Maintenance-Free
- 
  - Test Switch
  - Red (Power On) Indicator



XF



EXF

### Dimensions

- XF**  
 Height: 7.5"  
 Width: 12.3"  
 Depth: 2.0"
- EXF**  
 Height: 10.5"  
 Width: 12.3"  
 Depth: 2.0"

### Options

Add Suffix to Catalog Number

- 6** (2) 6VDC Lamps for AC/6VDC Remote Operation
- 12** (2) 12VDC Lamps for AC/12VDC Remote Operation
- 277** 277VAC Input
- 2CKT** (2) Independent AC Circuits
- OF** Open-Face Panel (Fiber Std.)
- REC** Recessed Housing (Single-Face XF Only)
- TP** Tamper-Proof Screws
- U** Universal Face (Additional Backplate - Double-Face Signs Only)

### Accessories

Order Separately

- 63** Wire Guard (for Single-Face Back Mount Only)
- P12** 12" Pendant Kit, White\*
- P12B** 12" Pendant Kit, Black\*
- \*Pendant Kits from 12" to 84" Available
- VDS** Vandal-Deterrent Shield (for Single-Face Back Mount XF Only)

## Ordering Information

XF Series	2 # Faces	R Letter Color	W** Stencil Color	W Housing Color	-6 Options
XF - AC EXF - Emer.	1 2	R ed G reen W hite	W hite* B lack M atte Chrome	W hite* B lack M atte Chrome	Factory Options

\*Standard

\*\*Background Panel Color on Open-Face Signs

