

Plastic Diffused LED Exits & Two-Headed Combo LED Exits

XKL



XKL/EXKL



2EXKL

Dimensions

XKL/EXKL

Height: 8.75
Width: 12.25"
Depth: 2.5"

2EXKL

With Heads on Side

Height: 10.2"
Width: 21.7"
Depth: 4.5"

With Heads on Top

Height: 15.7"
Width: 16.3
Depth: 4.5"

Options







Add Suffix to Catalog Number

For 2EXKL Only









- BLK Black Housing
- RMT Remote Capability Additional 12 Watts at 6VDC
- SD Self Diagnostic



Series Features

-  • 120/277 VAC Operation
-  • Maximum Input Rating (120 or 277VAC) 1.7 Watts Standard
-  • Light-Emitting Diodes – 25+ Year Life
-  • Illuminates with Uniform Color and Brightness
-  • Indirect Placement for Diffused Legend Output
- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
-  • Directional Chevron Snapouts
- White Finish
- Easy Installation
- UL Listed
- Flame-Retardant, High-Impact, Thermoplastic Housing
- Damp Location

Additional Emergency Unit Features

-  • Integrated Solid State System
-  • Constant Current, Controlled Automatic Charger Circuit
-  • Low-Voltage Battery Cutoff
-  • Brownout Sensitivity
-  • Initial Increased LED Brightness Level in Emergency Mode
-  • 2EXKL: (2) 6W Adjustable Lamp Heads
-  • EXKL: Sealed Nickel Cadmium Battery 10-Year Battery Warranty
-  • 2EXKL: Sealed Lead Cadmium Battery 5-Year Battery Warranty
-  • Test Switch
-  • LED (Power On) Indicator

Ordering Information

EXKL	2	R	W	W	U	-SD
Series	# Faces	Letter Color	Stencil Color	Housing Color	Universal	Options
XKL – AC EXKL – emer 2EXKL – combo	2	R ed G reen	W hite	W hite	Single- or Double-Face	Factory Options