

### Dimensions

### **STANDARD**

Height: 7.5" Width: 12.3" Depth: 2.0"

## NEW YORK CITY APPROVED

Height: 11.0" Width: 14.5" Depth: 2.3"

### Options Add Suffix to Catalog Number

-6 (2) 6VDC Lamps for AC/6VDC Remote Operation

-12 (2) 12VDC Lamps for AC/12VDC Remote Operation

-DMP Damp Location Listing (Damp

-DS Double LED Strips for Increased Illumination or 2 Independent AC Circuit Operation

-HI High-Intensity LEDs

-NY New York City Approved with 8" Letters

-REC Recessed Housing (Single-Face Only)

-TP Tamper-Proof Screws

-U Universal Face (Additional Backplate – Double-Face Signs Only)

# Accessories

Order Separately

63 Wire Guard (for Single-Face Back Mount Only)

P12W 12" Pendant Kit, White\*

P12B 12" Pendant Kit, Black\*

\*Pendant Kits from 12" to 84" Available

> S Vandal-Deterrent Shield (for Single-Face Back Mount Only)







## Series Features

• 120/277 VAC Operation



Maximum Input Rating (120 or 277VAC)

Standard 1.7 Watts DS Option 3.5 Watts



- Light-Emitting Diodes 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Ceiling, End or Back Mount
- Canopy
- Universal Stencil



- Directional Chevron Snapouts
- 20-Gauge Steel Housing
- · White Powder-Coat Finish
- · Easy Installation
- UL Listed

# Additional Emergency Unit Features



• Integrated Solid State System

- Constant Current, Controlled Automatic Charger Circuit
- · Low-Voltage Battery Cutoff
- Brownout Sensitivity



- Increased LED Brightness Level in Emergency Mode
- Sealed Nickel Cadmium Battery



- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free



- 3+ Hours Illumination in Emergency Mode\*
- Test Switch
- LED (Power On) Indicator

# Ordering Information

EXFL	1	R	W	W	-DS
XFL-AC Only EXFL – Emer.	# Faces 1 2	Letter Color Red Green	Stencil Color <u>W</u> hite <u>B</u> lack  PM Painted  Matte Chrome	Housing Color <u>W</u> hite* B lack PM Painted Matte Chrome	Option Factory Options

<sup>\*</sup>Longer Illumination Times Available. Consult Factory.